

DA-65W

DAonWindows - range
2D-graphical controller
for hydraulic press brakes

Delem



Proven embedded reliability

DAonWindows controllers feature an embedded, real-time Windows operating system for maximum reliability. Smooth start-ups ensured, even after instant shut off.

The DA-65W press brake controller combines **user-friendliness** with efficient programming and reliability. This, combined in one strong package, increasing machine productivity.

The latest graphics technologies enable **real scale representation** within Delem's familiar intuitive user interface.

The system offers 2D graphical programming that include **automatic bend sequence calculation and collision detection**. Together with self-learning databases this will lead to a good result of the desired product. The **full 3D** machine set-up includes multiple tool stations and offers true feedback on product feasibility and handling.

Highly effective control algorithms optimise the machine cycle and minimise set-up time. This makes using press brakes easier, more efficient and more versatile than ever.

Windows® networking ensures **easy integration** in your production network. The controller can be accessed from anywhere in the network and product data can be stored at the desired network locations.

Housed in a tough and sturdy cabinet, the DAonWindows control is based on **state-of-the-art industrial electronics** and equipped with a high quality colour LCD (TFT) screen.

Delem's **Modusys** concept and its built-in PLC allows you to add functionality, providing maximum scalability and adaptivity.

DA-65W featuring:

- 2D graphical programming
- **3D visualisation** in production mode
- 10" TFT color display
- Full Windows suite
- Integrated OEM-panel
- USB keyboard & mouse interface
- User specific application support within the controllers' multitasking environment
- Sensor bending & correction interface

Technical Specifications DA-65W

Product configuration

Standard

- Colour LCD display
- 10" TFT, high brightness
- 800 x 600 pixels, 16 bit
- 600 MHz microprocessor
- Memory capacity 128 MB
- Product and tools memory 64 MB
- 3D graphics acceleration
- Standard Windows® networking
- Emergency button
- Integrated OEM-panel
- USB flash memory drive

Field options

- Part support control
- X1-X2 angle programming
- 2nd Modusys bus (HSB)
- Barcode reader interface
- Frame deflection compensation
- Sensor bending & correction interface

Ordering information

- DA-65We



Panelline concept

Technical specifications

General

- Real-time embedded Windows® OS
- Stable, multitasking environment
- Instant Shut Off
- Delem Modusys compatible
- Tandem operation

Programming functions

- Alphanumeric product naming, up to 25 characters
- 2D real-scale product programming and visualisation
- Automatic bend sequence calculation in 2D and 3D
- Easy graphical bend sequence swap and move
- Front part support visualisation
- One page programming table
- Graphical product and tool selection
- Programmable axis speed
- Free material programming
- Program repeat max. 9,999
- Number of steps up to 99
- Step repeat, 99 max.
- Product & tool search filter
- Millimetres / inches
- kN / Ton selection

Tooling

- Graphical tool configuration
- Multiple tool station set-ups
- Tool segmentation visualisation
- Alphanumeric tool identification, up to 25 character
- Free graphical tool programming
- Tool adapter support

Computed functions

- Tooling safety zones
- Press force
- Bend allowance
- Crowning adjustment
- Developed length
- Bottoming force
- Hemming force
- Auto bumping calculation
- Radius programming
- Learned bend allowance table
- Angle correction database

Miscellaneous

- Machine time + stroke counter
- Error messaging system
- Diagnostic program

- Integrated help functions
- Handwheel movement of all axes
- "Teach-in" on Y and auxiliary axes
- Stock counter
- User specific applications support
- Sequencer functionality (PLC)
- Optional SoftPLC according to IEC61131-3 standard

Interfaces

- Modusys bus (HSB) up to 8 modules
- DNC-RS 232C, bi-directional (2x)
- Network interface (100 Mb / 10Mb)
- USB (2x) for external devices
- Safety PLC interfacing

Enhanced functions

- Word processor (WordPad)
- Email client (POP3)
- Internet Explorer (web browser)
- Remote Terminal Client
- Remote diagnosis
- Analysis Tool
- PDF viewer
- On screen keyboard

Delem

Luchthavenweg 42, 5657 EB Eindhoven
The Netherlands www.delem.com
T: +31(0)40 2552969, F: +31(0)40 2551923

Everything under control