

剪板机技术参数

机床型号	剪切厚度(mm)	剪切宽度(mm)	剪切角度	行程次数	后档料距离 (mm)	电机(kw)	压料缸数
HTS-1645	4.5	1580	1°	23	1250	15	10
HTS-3045	4.5	3070	1° 25'	24	1250	18.5	18
HTS-3065	6.5	3070	1°	23	1250	18.5	18
HTS-4065	6.5	4070	1°	20	1250	22	23
HTS-3010	10	3070	1° 50'	21	1250	22	18
HTS-4010	10	4070	1° 25'	14	1250	22	23
HTS-6010	10	6100	1° 25'	18	1250	55	32
HTS-3013	13	3070	2°	18	1250	37	16
HTS-4013	13	4070	1° 50'	17	1250	45	22
HTS-6013	13	6100	1° 50'	16	1250	55	32
HTS-7013	13	7000	1° 50'	15	1250	55	36
HTS-3016	16	3070	2°	17	1250	45	16
HTS-4016	16	4070	1° 50'	15	1250	55	22
HTS-3020	20	3070	2°	13	1250	55	16
HTS-3025	25	3070	2°	12	1250	55	16

3. W67K 系列 电液同步数控折弯机参数表

机床型号	折弯力 (KN)	可折板 宽 (mm)	立柱 间距 (mm)	开启 高度 (mm)	喉口 深度 (mm)	滑块 行程 (mm)	油缸 缸径 / 杆径×行 程 mm	模 具		主电机 功率 (KW)	外形尺寸(mm) (长*宽*高)	重量 (kg)
								上模高× 厚 mm	下模断面尺寸 mm			
W67K-320/3200												
W67K-320/4000												
W67K-320/5000												
W67K-320/6000												
W67K-400/3200	4000	3200	2700	500	400	250	Φ 310/ Φ 290×250 26.5MPa	195×40	150×150 V=110	30	3465×3215×4250	25600
W67K-400/4000	4000	4000	3300								4265×3215×4370	27800
W67K-400/5000	4000	5000	4000								5265×3215×4710	33500
W67K-400/6000	4000	6000	5000								6265×3215×5020	37500
W67K-400/7000	4000	7000	5600								7265×3215×5355	42800
W67K-400/8000	4000	8000	6600								8250×3260×5960	54800
W67K-500/3200	5000	3200	2700	600	450	300	Φ 350/ Φ 330×300 26MPa	195×40	150×150 V=110	37	3465×3450×4665	33200
W67K-500/4000	5000	4000	3300								4265×3450×4660	36200
W67K-500/5000	5000	5000	4000								5265×3450×4750	40500
W67K-500/6000	5000	6000	5000								6265×3450×5070	46200
W67K-500/7000	5000	7000	5600								7265×3450×5400	50100
W67K-600/4000	6000	4000	3300	650	500	350	Φ 380/ Φ 360×350	220×38	180×180	45	4265×3825×5160	48000

W67K-600/5000	6000	5000	4000				26.5MPa		V=130		5265×3825×5335	54800
W67K-600/6000	6000	6000	5000				6265×3825×5560		60000			
W67K-600/7000	6000	7000	5600				7265×3825×6080		66500			
W67K-700/4000	7000	4000	3300	700	600	350	φ 400/ φ 380×350 26MPa	260×40	180×180 V=140	45	4285×3785×5200	51000
W67Y-700/5000	7000	5000	4100								5285×3785×5330	56500
W67K-700/6000	7000	6000	5000								6285×3785×5530	64400
W67K-700/7000	7000	7000	5800								7285×3785×6030	71500
W67K-800/4000	8000	4000	3200	820	600	400	φ 450/ φ 430×400 25Mpa 油箱容量≥1300L 滑块速度: 驱进 70mm/s 压制 9mm/s 返程 80mm/s	360×42 (R3)	180×180 V=24、36、48、 60、90、140 工作台宽度: 400mm	2×37	4345×4140×5540	65000
W67K-800/5000	8000	5000	4000								5345×4140×5790	73000
W67K-800/6000	8000	6000	5000								4345×4140×6090	82000
W67K-800/7000	8000	7000	5800								7345×4140×6390	89000
W67K-800/8000	8000	8000	6800								8345×4140×7020	103000
W67K-800/9000	8000	9000	7400								8345×4140×7400	116000
W67K-800/10000	8000	10000	8000								10345×4140×7900	124000
W67K-800/12000	8000	12000	9000								12345×4140×8600	146000
W67K-1000/4000	10000	4000	3200	900	800	400	φ 500/ φ 470×400 25.5Mpa 油箱容量≥1600L 滑块速度: 驱进 80mm/s 压制 9mm/s 返程 75mm/s	模柄: 320× 50 模头: 80× 60 (R5)	200×200 V=24、36、48、 60、90、160 或可调式下模 工作台宽度: 400mm	2×45	4345×4540×6090	82000
W67K-1000/5000	10000	5000	4000								5345×4540×6290	91000
W67K-1000/6000	10000	6000	5000								6345×4540×6590	101000
W67K-1000/7000	10000	7000	5800								7345×4540×6890	112000
W67K-1000/8000	10000	8000	6800								8345×4540×7350	125000
W67K-1000/9000	10000	9000	7400								9345×4540×7750	136000
W67K-1000/10000	10000	10000	8000								10345×4540×8150	148000
W67K-1000/12000	10000	12000	9000								12345×4540×8750	170000
W67K-1200/4000	12000	4000	3200	900	850	400	φ 560/ φ 520×400	模柄: 320×	可调式下模	2×55	4280×5090×6450	93000

W67K-1200/5000	12000	5000	4000				25Mpa	54	模块:		5280×5090×6550	106000		
W67K-1200/6000	12000	6000	5000				油箱容量≥2000L	模头: 80×	100×50		6280×5090×6750	116000		
W67K-1200/7000	12000	7000	5800				滑块速度:	60	模座:		7280×5090×7350	128000		
W67K-1200/8000	12000	8000	6800				驱进 75mm/s	(R5)	440×200		8280×5090×7550	142000		
W67K-1200/9000	12000	9000	7400				压制 7.5mm/s		Vmax=160		9280×5090×7550	154000		
W67K-1200/10000	12000	10000	8000				返程 70mm/s		工作台宽度:		10280×5090×8000	166000		
W67K-1200/12000	12000	12000	9000						500mm		12280×5090×9000	195000		
W67K-1500/5000	15000	5000	4000	1000	900	600	Φ620/Φ590×600	模柄: 320×	可调式下模	2×55	5280×5390×7080	130000		
W67K-1500/6000	15000	6000	5000				25Mpa				60	模块:120×50	6280×5390×7280	141000
W67K-1500/7000	15000	7000	5800				油箱容量≥3600L				模头: 80×	模座:460×230	7280×5390×7580	154000
W67K-1500/8000	15000	8000	6800				滑块速度:				70	Vmax=160	8280×5390×7880	169000
W67K-1500/9000	15000	9000	7400				驱进 65mm/s				(R6)	Vmin=40	9280×5390×8080	182000
W67K-1500/10000	15000	10000	8000				压制 6.5mm/s					工作台宽度:	10280×5390×8300	196000
W67K-1500/12000	15000	12000	9000				返程 65mm/s					500mm	12280×5390×8900	223000
W67K-1600/5000	16000	5000	4000	1100	1000	600	Φ640/Φ610×600	模柄: 340×	可调式下模	2×55	5280×5490×7230	140000		
W67K-1600/6000	16000	6000	5000				25Mpa				60	模块:120×50	6280×5490×7430	152000
W67K-1600/7000	16000	7000	5800				油箱容量≥3800L				模头: 100×	模座:460×240	7280×5490×7730	166000
W67K-1600/8000	16000	8000	6800				滑块速度:				70	Vmax=160	8280×5490×8030	182000
W67K-1600/9000	16000	9000	7200				驱进 60mm/s				(R6)	Vmin=40	9280×5490×8230	197000
W67K-1600/10000	16000	10000	8000				压制 6mm/s					工作台宽度:	10280×5490×8430	211000
W67K-1600/12000	16000	12000	9000				返程 60mm/s					500mm	12280×5490×9200	242000
W67K-2000/5000	20000	5000	4000	1200	1100	600	Φ720/Φ680×600	模柄: 400×	可调式下模	2×75	5280×5940×7870	184000		
W67K-2000/6000	20000	6000	5000				25Mpa				70	模块:140×50	6280×5940×8070	198000

W67K-2000/7000	20000	7000	5800				油箱容量≥4800L	模头: 100×	模座:560×270		7280×5940×8270	216000
W67K-2000/8000	20000	8000	6800				滑块速度:	70	Vmax=240		8280×5940×8470	232000
W67K-2000/9000	20000	9000	7400				驱进 60mm/s	(R6)	Vmin=60		9280×5940×8670	249000
W67K-2000/10000	20000	10000	8000				压制 6mm/s		工作台宽度:		10280×5940×8870	266000
W67K-2000/12000	20000	12000	9000				返程 60mm/s		600mm		12280×5940×9560	302000
W67K-2400/6000	24000	6000	5000				φ 800/ φ 760×600	模柄: 500×	可调式下模		6280×7080×8980	252000
W67K-2400/7000	24000	7000	5800				25Mpa	80	模块:150×50		7280×7080×9180	271000
W67K-2400/8000	24000	8000	6800				油箱容量≥6000L	模头: 100×	模座:560×280		8280×7080×9480	294000
W67K-2400/9000	24000	9000	7400	1300	1200	600	滑块速度:	80	Vmax=240	2×75	9280×7080×9480	313000
W67K-2400/10000	24000	10000	8000				驱进 60mm/s	(R6)	Vmin=60		10280×7080×9880	335000
W67K-2400/12000	24000	12000	9000				压制 6mm/s		模座:740×300		12280×7080×10280	377000
							返程 60mm/s		Vmax=340			
									Vmin=60			

--	--	--	--	--	--	--	--	--	--	--	--	--